



® Safety Data Sheet

The Armor All/STP Products Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

1. Product And Company Identification

Product Name: ARMOR ALL® Extreme Tire Shine Aerosol

Responsible Party: The Armor All/STP Products Company
44 Old Ridgebury Road
Suite 300
Danbury, CT 06810

Information Phone Number: +1 203-205-2900

Emergency Phone Number:

For Medical Emergencies, call 1-866-949-6465 / +1 303-389-1332 (Outside US and Canada)
For Transportation Emergencies, call 1-800-424-9300 (Chemtrec) +1-703-527-3887 for
Outside US and Canada (call collect)

SDS Date Of Preparation: 04/11/2015

Product Use and Uses Advised Against: Automotive maintenance product – For consumer and professional use

2. Hazards Identification

Note: This product is a consumer product and is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.

GHS Classification:

Physical:	Health:
Flammable Aerosol Category 1 Gases Under Pressure: Compressed Gas	Non Hazardous

GHS Label Elements:



Danger!

Statements of Hazard

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.

Prevention

Keep away from heat, sparks, open flames, and hot surfaces.
No smoking.
Do not spray on an open flame or other ignition source.
Pressurized Container. Do not pierce or burn, even after use.
Protect from sunlight. Do not exposure to temperatures exceeding 50°C / 122°F.

Hazards not otherwise specified: None

Percentage of unknown toxicity: N/A



® Safety Data Sheet

The Armor All/STP Products Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

3. Composition/Information On Ingredients

Component	CAS No.	Amount
Propellant (propane, isobutane)	74-98-6 / 75-28-5	1 - 9%
Non-Hazardous Ingredients	Mixture	>91 – 99%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First Aid Measures

Inhalation: If symptoms of exposure develop, remove to fresh air. Seek medical attention if breathing problems or irritation persist.

Skin Contact: Rinse skin with plenty of water. If skin irritation or redness develops, seek medical attention.

Eye Contact: Flush eyes with plenty of water. If irritation or other symptoms persist, seek medical attention.

Ingestion: If the victim is fully conscious, have them drink a glass of water. Get medical assistance by calling a doctor or poison center. Never give anything by mouth to a person who is unconscious or drowsy.

Most Important Symptoms: Direct eye contact may cause mild irritation.

Indication of Immediate Medical Attention/Special Treatment: Immediate medical attention should not be required.

5. Firefighting Measures

Suitable (and Unsuitable) Extinguishing Media: Use dry chemical, carbon dioxide, foam, or water spray.

Specific Hazards Arising from the Chemical: Contents under pressure. Keep away from ignition source and open flames. Exposure of containers to heat and flames can cause them to rupture, often with violent force. Thermal decomposition will generate oxides of carbon, and silicon; and formaldehyde.

Special Fire Fighting Procedures: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures: Eliminate all sources of ignition. Ventilate area with explosion proof equipment. Wear appropriate protective clothing and equipment.

Methods and Materials for Containment and Clean-Up: Place leaking can in a pail in a well-ventilated area away from ignition sources until pressure has dissipated. Collect liquid using inert material and place into a suitable container for disposal.

Environmental Precautions: Prevent entry into storm sewers and waterways. Report spill as required by local and national regulations.



® Safety Data Sheet

The Armor All/STP Products Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

7. Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes. Avoid prolonged contact with skin, and clothing. Use with adequate ventilation. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children. Do not puncture or incinerate containers.

Conditions for Safe Storage, Including any Incompatibilities: Store in a cool, well-ventilated area, away from incompatible materials. Do not store in direct sunlight or above 120°F. **U.F.C. (NFPA 30B) Level 1 Aerosol.**

8. Exposure Controls / Personal Protection

Exposure Guidelines:

CHEMICAL	EXPOSURE LIMIT
Propane	1000 ppm TWA OSHA PEL
Isobutane	1000 ppm STEL ACGIH TLV
Non-Hazardous Ingredients	None Established

Appropriate Engineering Controls: General ventilation should be adequate for normal use.

Personal Protective Equipment

Respiratory Protection: None under normal use conditions.

Gloves: None normally required.

Eye Protection: None required for normal use. Avoid eye contact.

Other Protective Equipment/Clothing: None required under normal use conditions.

9. Physical and Chemical Properties

Appearance And Odor: Liquid with a slight odor in an aerosol can.

Physical State: Liquid-based aerosol	Odor Threshold: Not determined
pH: ~9.5 (Liquid component)	Specific Gravity: ~1 (Liquid Component)
Initial Boiling Point/Range: Not determined	Vapor Pressure: Not determined
Melting/Freezing Point: Not determined	Vapor Density: Not determined
Solubility In Water: Not determined	Percent Volatile: Not determined
Viscosity: 134.5 cPs (liquid component)	Evaporation Rate: Not determined
Relative Density: Not determined	VOC Content: Not determined
Coefficient Of Water/Oil Distribution: Not determined	Autoignition Temp: Not determined
Flash Point: Not determined for liquid component. Propellant is a flammable gas.	Flammability (solid, gas): Not applicable
Flammability Limits: LEL: 1.8% (Isobutane) UEL: 9.5% (Propane)	Decomposition Temperature: Not available



® Safety Data Sheet

The Armor All/STP Products Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

10. Stability and Reactivity

Reactivity: Not normally reactive.

Chemical Stability: Stable under normal storage and handling conditions.

Conditions to Avoid: Keep away from excessive heat, sparks and open flames. Containers may rupture at temperatures > 120°F (48.8°C).

Incompatible Materials: Strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition will generate oxides of carbon, and silicon; and formaldehyde.

11. Toxicological Information

Potential Health Effects:

Acute Hazards:

Inhalation: No adverse effects expected from the normal use of this product.

Skin Contact: Prolonged or repeated contact may cause mild irritation in some individuals

Eye Contact: Direct contact may cause mild eye irritation with redness and tearing.

Ingestion: Ingestion is an unlikely route exposure for aerosol products. Swallowing may cause gastrointestinal disturbances.

Chronic Effects: None known

Carcinogenicity Listing: None of the components is listed as a carcinogen or potential carcinogen by IARC, NTP, ACGIH or OSHA.

Numerical Measures of Toxicity:

Propane: LC50 Rat inhalation >800,000 ppm

Isobutane: LC50 Rat inhalation 658 mg//4 hr.

12. Ecological Information

Ecotoxicity: No ecotoxicity data is currently available for product.

Persistence and Degradability: No data available for product.

Bio accumulative Potential: No data available for product.

Mobility in Soil: No data available for product.

Other Adverse Effects: No data available



® Safety Data Sheet

The Armor All/STP Products Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

13. Disposal Considerations

Dispose of in accordance with all local, state/provincial and federal regulations. Offer empty containers for recycling.

14. Transport Information

DOT Hazardous Materials Description: UN1950, Aerosols, Class 2.1, Ltd Qty

IMDG Dangerous Goods Description: UN1950, Aerosols, 2.1, Ltd Qty

IATA International Air Transport Association: UN1950, Aerosols, Class 2.1, Ltd Qty

15. Regulatory Information

United States:

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CERCLA Section 103: This product has no RQ. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Fire Hazard, Sudden Release of Pressure

SARA 313: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

Canada:

Canadian Environmental Protection Act: All of the ingredients are listed on the Canadian DSL.

This SDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the SDS contains all of the information required by the CPR.

16. Other Information

NFPA Rating (NFPA 704):	Health: 1	Fire: 4	Instability: 0
HMIS Rating:	Health: 1	Fire: 2	Physical Hazard: 0

REVISION SUMMARY: April 11, 2015 Update to GHS SDS format and formulation change: Changes to all sections.

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH